



PRESSURE CLEANERS



Made in Australia
SINCE 1982

SW2030

Hot/Cold Water Cleaner with two stainless steel heating coils



Specifications

- ➔ 200 bar (2900 psi) pump pressure
- ➔ 263 bar (3825 psi) EWP pressure (optional)
- ➔ 30 Litres Per Minute pump volume
- ➔ 415 V 15 hp Electric motor
- ➔ 1450 rpm low speed pump
- ➔ 32 amp plug 3 phase
- ➔ Temperatures up to 90°
- ➔ Heavy duty machine

Standard Equipment

- ➔ Two Stainless steel heating coils
- ➔ Water cooling tank and low level water switch
- ➔ 10 Metre high pressure hose
- ➔ Insulated on/off pistol assembly
- ➔ Dual lance with high / low pressure valve
- ➔ Accessible control panel with E-stop
- ➔ Bypass shutdown timer
- ➔ Operating and Maintenance manual

Features

Interpump with ceramic pistons and brass head

Water cooling tank and low level water switch

Two Stainless Steel, seamless heating coils

Pressure gauge

3 Stage zinc annealed, and powder coated chassis and frame with forklift lifting points

Adjustable thermostat for hot water temperature control

Bypass shutdown timer

Benefits

Longer pump life and reduced maintenance costs

Protects the pump from overheating in by-pass (trigger closed) mode and prevents machine running dry

Corrosion resistant for longer heating coil life

Easily monitor pump performance

Resistant to corrosion and able to be moved safely and easily

Set the ideal temperature for any application

Increases life of the machine by shutting down when not in use

For more information,
please visit our website

spitwater.com.au

TOUGH + READY

CREATED BY **OTTICO**