

HT18-160E GT

High Temperature Water Cleaner



Picture showing wall mount option

Specifications

- ⇒ 2400 P.S.I. (160 Bar) pump pressure
- ⇒ 3525 P.S.I. turbo pressure (optional)
- ⇒ 18 Litres Per Minute pump volume
- ⇒ 415 Volt 7.5 H.P. electric motor
- ⇒ 1450 RPM low speed pump
- ⇒ 20 amp plug Three phase
- ⇒ Inlet water temperature up to 80°
- ⇒ Heavy duty machine

Standard Equipment

- ⇒ 10 Metres high pressure hose
- ⇒ Insulated on/off pistol assembly
- ⇒ Double lance assembly with adjustable pressure
- ⇒ Chemical injector with 2M hose with filter
- ⇒ Operators and parts manuals

Features	Benefits
Interpump with ceramic pistons and brass head	Non-corrosive pump head to extend pump life and reduce maintenance costs
Delayed total stop system	Power on when trigger is pulled
Inlet water filter	Stops debris from scoring pistons and seals
Pressure gauge	Easily monitor pump performance
Galvanised base with stainless steel cover	Corrosion resistant – Ideal for wet areas Wall & floor mounted options available

For more information,
please visit our website

spitwater.com.au