



SPACE HEATERS



IP110

Indirect Fired Diesel Heater



Specifications

- ⇒ Heat output 110 kW / 375,335 BTU/h
- ⇒ 135 L fuel tank
- ⇒ 9.2 kg/h fuel consumption
- ⇒ 240 V 15 amp plug
- ⇒ 3M minimum safe distance
- ⇒ 5300 m³/h Airflow
- ⇒ 149 kg (empty)

Standard Equipment

- ⇒ Robust compact design
- ⇒ All Steel constructed tank, body & trolley
- ⇒ Automatic Ignition
- ⇒ Large fuel tank with drain plug
- ⇒ Ergonomic handle & solid wheels
- ⇒ Two stage Low/High heat selection
- ⇒ Chimney exhaust connection

Features	Benefits
Internal stainless steel burner combustion chamber	Allows external surface to stay cool
Safety Thermostat & Flame-out control	Shuts down when internal fault is detected
Built-in room thermostat with LED display	Efficient and consistent room temperature control whilst reducing the fuel consumption
Low Maintenance burner system	Lowering maintenance costs
Socket for optional accessory connection	Allows for an additional thermostat or automatic timer to be used
Inlet air recirculation (when used with optional ducting)	Allows for accelerated heating time

For more information, please visit our website

spitwater.com.au

TOUGH + READY
CREATED BY OTTICO