





SW15-200SDES

Silent Diesel Hot/Cold Water Cleaner



Specifications

- 200 bar (2900 psi) pump pressure
- 280 bar (4061 psi) Turbo pressure (optional)
- ⇒ 15 L/min pump water volume
- ⇒ 13 hp Hatz Silent diesel engine
- → 1800 rpm pump
- → 12 V Diesel burner system
- Temperatures up to 90°
- Heavy duty machine

Standard Equipment

- ⇒ Stainless steel heating coil
- ♦ Water cooling tank
- Insulated on/off pistol assembly
- Dual lance with high / low pressure valve
- Adjustable chemical injector with 10 L container
- Operating and Maintenance Manual

Features	Benefits
Hatz Silent Diesel engine	Very low noise level, super quiet operation
Interpump with ceramic pistons and brass head	Longer pump life and reduced maintenance costs
Water cooling tank and low level water switch	Protects the pump from overheating in by-pass (trigger closed) mode and prevents machine running dry
Stainless Steel, seamless heating coil	Corrosion resistant for longer heating coil life
3 Stage zinc annealed, and powder coated chassis and frame with forklift lifting points	Resistant to corrosion and able to be moved safely and easily
Spitwater 'Oz-Tuff' belt drive	Efficient and reliable transfer of power, needs less power to drive, uses less fuel
Emergency stop and battery isolator	Enhanced operator safety and machine protection

Pressure gauge and hour meter

Easy monitoring of machine performance

For more information, please visit our website

spitwater.com.au

