

## 13-180HS

Hot/Cold Water Cleaner



### Specifications

- ⇒ 180 bar (2610 psi) pump pressure
- ⇒ 258 bar (3741 psi) EWP pressure (optional)
- ⇒ 13 Litres Per Minute pump volume
- ⇒ 415 V 5 hp Electric motor
- ⇒ 2800 rpm pump
- ⇒ 10 amp plug 3 phase
- ⇒ Temperatures up to 90°
- ⇒ Medium duty machine

### Standard Equipment

- ⇒ 8 Metres high pressure hose
- ⇒ Insulated on/off pistol assembly
- ⇒ Double lance assembly
- ⇒ High and Low pressure mode
- ⇒ Adjustable chemical injector with bottle
- ⇒ Stainless steel heating coil
- ⇒ Operating and Maintenance manual

Features	Benefits
Interpump with ceramic pistons and brass head	Non-corrosive pump head to extend pump life and reduced maintenance costs
Water cooling tank	Reduces potential damage to the pump in bypass
Inlet water filter	Stops debris from scoring pistons and seals
3 Stage powder coated zinc annealed chassis	Resistant to corrosion
Adjustable thermostat for hot water temperature control	Set the ideal temperature for any application
Stainless steel heating coil	Corrosion resistance extends the life of the heating coil

For more information,  
please visit our website

[spitwater.com.au](http://spitwater.com.au)