

PRESSURE CLEANERS







Specifications	Standard Equipment
 250 Bar (3626 psi) pump pressure 330 Bar (4786 psi) EWE turbo pressure (optional) Pump volume: 15 L/min at 1450 rpm – 42 L/min Hyd. flow 20 L/min at 1950 rpm – 56.5 L/min Hyd. flow 26 cc Hydraulic motor capacity: 130 Bar (1885 psi) Hyd. pressure Heavy duty machine 	 Interpump EVO-3 brass head pump HYPACK26 hydraulic motor with case drain VB280 unloader valve VS350 safety valve VS350 safety valve Pressure gauge Inlet water filter Operating & Maintenance Manual (Optional hose, gun and lance)
Features	Benefits
Compact design	Able to fit in tight spaces on purpose-built vehicles
Variable water flow from 15 L/min to 20 L/min (dependant on hydraulic capacity)	Ideal for different applications from concrete pumps and mixers to hydro-excavation and ag sprayers
Interpump with brass head and ceramic pistons	Non-corrosive pump head, longer pump life and lower maintenance costs
Italian made hydraulic motor with case drain	High quality and reliability
Heavy duty unloader valve and safety valve with pressure gauge	High quality, reliability and complete operational safety

For more information, please visit our website



