



PRESSURE CLEANERS



Made in Australia
SINCE 1982

HP25-4000E

Cold Water Cleaner



Specifications

- ⇒ 400 bar (5800 psi) pump pressure
- ⇒ 25 Litres Per Minute pump volume
- ⇒ 30 hp Kubota water cooled diesel motor
- ⇒ 1450 rpm low speed pump
- ⇒ Heavy duty machine

Standard Equipment

- ⇒ 10 Metres high pressure hose
- ⇒ Insulated on/off pistol assembly
- ⇒ Single lance assembly with fixed fan jet
- ⇒ Large stainless steel water tank
- ⇒ Low level water cut off
- ⇒ Operating and Maintenance manual

Features	Benefits
Interpump with ceramic pistons and brass head	Non-corrosive pump head to extend pump life and reduced maintenance costs
Oz-tuff belt drive	15% more power available than a gearbox and no more gearbox oil leaks (maintenance free)
Water cooling tank with inlet water filter	Reduces potential damage to the pump in bypass, protects the pump from debris
External radiator overflow tank and detergent tank	Ease of daily checks and maintenance
Pressure gauge	Easily monitor pump performance
3 Stage powder coated zinc annealed chassis and Frame with forklift lifting points	Resistant to corrosion
12 V Enclosed battery Isolator and emergency stop	Keeps the battery in good condition and protects the operator in an emergency

For more information,
please visit our website

spitwater.com.au

TOUGH + READY
CREATED BY **OTTICO**